





REV	ECN	SIGN	DATE	DESCRIPTION
1.0	V0	K. ZHAO	10/21/2021	/



3P 4P 6P 8P

Pin Assignments

- NOTES:
1. RoHS Compliant
 2. Levels of protection: IP67
 3. Installation mode: Solder, Front fastened
 4. Operating temperature: -40°C~105°C
 5. Applicable Panel: Panel Hole
- For Panel Thickness Max: 4.5mm

6. Connector tolerances:





linear dimension	≡	□	∥	⊥
variable range	to over	to over	to over	to over
10	18	30	50	80
30	50	80	120	160
50	80	120	160	200
80	120	160	200	250
120	160	200	250	300
160	200	250	300	350
200	250	300	350	400
tolerance	±0.15	±0.25	±0.35	±0.55
	±0.80	±1.05	±1.30	0.5
	0.025	0.06	0.12	0.4

S5D-M8A - XXP - FF-SL7000 - 00AH

Standard

Coding: A,B

Poles



Panel Hole

Remark: This drawing is a controlled document for Cymann. All specifications are subject to change without prior notice.

PARAM:	DATE:	PARAM:	DATE:
DESIGNER: K. ZHAO	10/21/2021	PART NO.: S5D-M8A-XXP-FF-SL7000-00AH	
CHECKER: C. LU	10/21/2021	TITLE: M8A female, Front Fastened Socket	
APPROVER: H. JIANG	10/21/2021	CUSTOMER: /	

Cymannu 囍字電子

NINGBO CHANGYU ELECTRONICS MANUFACTURING CO., LTD

Email: sales@cymannu.com WWW.CYMANNU.COM