REV	ECN	SIGN	DATE	DESCRIPTION
1.0	V0	K. ZHAO	05/23/2021	











NOTES:

1.UL Standard

Application	B	C	D
Rate voltage(V)	300	/	300
Rate current(A)	12	/	10
Rate impulse voltage(KV)	1.6		

2.IEC Standard

Pollution degree	2	2	3
Overvoltage category	II	III	III
Rate impulse voltage(KV)	4	4	4
Rate voltage(V)	320	320	250
Rate current(A)	15		

3.Pitch : 5.08 mm

4.Operating temperature: −40°C~+105°C

5.RoHS Compliance

6.Material: Housing PA66,UL94V−0
Pin copper alloy,Sn plated
Nut copper alloy

CYE220RM − 508 − XXP − 1YY − 000A

- CYE220RM: Series No
- 508: Pitch
- XXP: Poles
- 1YY: Single Pitoh
- 1Y: Color
- 000A: Standard

Color: 1Y,white
2Y,black
3Y,grey
4Y,green
5Y,blue
6Y,yellow
7Y,transparent
8Y,brown

	linear dimension							⌯	—	⏥	//	⊥
variable range	to 10	over 18 to 30	over 30 to 50	over 50 to 80	over 80 to 120	over 120 to 160	over 160 to 200	all	to 5	over 5 to 30	over 30 to 120	over 120 to
tolerance	±0.15	±0.25	±0.35	±0.45	±0.60	±0.75	±0.90	0.5	0.025	0.06	0.12	0.4

Remark: This drawing is a controlled document for Cymanu. All specifications are subject to change without prior notice.

		DRAWN: K. ZHAO	DATE: 05/23/2021	PART NO: CYE220RM-508-XXP-1YY-000A
SIZE: A4	SCALE: 2 : 1	CHECKED: C. LU	DATE: 05/23/2021	TITLE: Plug in connector
UNIT:mm	SHEET: 1 / 1	APPROVED: H. JIANG	DATE: 05/23/2021	CUSTOMER:

Cymanu® 暘宇電子
NINGBO CHANGYU ELECTRONICS MANUFACTURING CO., LTD
Email: sales@cymanu.com WWW.CYMANU.COM