





REV	ECN	SIGN	DATE	DESCRIPTION
1.0	V0	K. ZHAO	05/18/2021	



NOTES:
1. UL Standard

Application	B	C	D
Rate voltage(V)	300	/	300
Rate current(A)	8	/	8
Rate impulse voltage(KV)	1.6		


Wire range : 26 ~ 16 AWG

2. IEC Standard

Pollution degree	2	2	3
Overvoltage category	II	III	III
Rate impulse voltage(KV)	2.5	2.5	2.5
Rate voltage(V)	250	160	160
Rate current(A)	7		

Wire range : 0.2 ~ 1.5 mm²

- Pitch : 3.50 mm, Poles : N = 02~24 P
- Stripping length : 8 ~ 10mm
- Operating temperature: -40°C~+105°C
- RoHS Compliance
- Material: Housing PA66, UL94V-0
Clamp copper alloy, Sn plated



Remark: This drawing is a controlled document for Cymannu. All specifications are subject to change without prior notice.

linear dimension	≡	—	□	//	⊥
over 18 to 30	over 30 to 50	over 50 to 80	over 80 to 120	over 120 to 160	over 160 to 200
tolerance ±0.15	±0.25	±0.35	±0.45	±0.60	±0.75
all	to 5	over 5 to 30	over 30 to 120	over 120 to 200	0.4
0.5	0.025	0.06	0.12	0.4	

SIZE	SCALE	CHECKED	DATE	DATE	DATE
A4	3 : 2	C. LU	05/18/2021	05/18/2021	05/18/2021
UNIT: mm	SHEET: 1 / 1	APPROVED: H. JIANG			

NINGBO CHANGYU ELECTRONICS MANUFACTURING CO., LTD
 Email: sales@cymannu.com WWW.CYMANNU.COM