




REV	ECN	SIGN	DATE	DESCRIPTION
1.0	V0	K. ZHAO	05/12/2021	




NOTES:  
1. UL Standard

Application	B	C	D
Rate voltage(V)	300	/	300
Rate current(A)	12	/	10
Rate impulse voltage(KV)	1.6		

Wire range : 26 ~ 14 AWG  
2. IEC Standard

Pollution degree	2	2	3
Overvoltage category	II	III	III
Rate impulse voltage(KV)	4	4	4
Rate voltage(V)	320	250	250
Rate current(A)	15		

- Wire range : 0.2 ~ 1.5 mm<sup>2</sup>
- 3. Torque: 0.5 N.m(4.43Lb.in)
- 4. Pitch : 5.08 mm, Poles : N = 02/03 P
- 5. Stripping length : 6 ~ 7 mm
- 6. Operating temperature: -40°C~+105°C
- 7. RoHS Compliance
- 8. Material: Housing PA66, UL94V-0  
Screws M3 Steel, Cr plated  
Pin copper alloy, Sn plated



- Color: 1Y, white  
2Y, black  
3Y, grey  
4Y, green  
5Y, blue  
6Y, yellow  
7Y, transparent  
8Y, brown

Remark: This drawing is a controlled document for Cymann. All specifications are subject to change without prior notice.

linear dimension	≡	—	□	//	⊥
over 18 to 30	over 30 to 50	over 50 to 80	over 80 to 120	over 120 to 160	over 160 to 200
tolerance ±0.15	±0.25	±0.35	±0.45	±0.60	±0.75
all to 5	all to 5	all to 5	all to 5	all to 5	all to 5
0.025	0.06	0.12	0.12	0.12	0.4

SIZE: A4	SCALE: 2 : 1	DRAWN: K. ZHAO	DATE: 05/12/2021	PART NO.: CYE112-508-XXP-1YY-000A
UNIT: mm	SHEET: 1 / 1	CHECKED: C. LU	DATE: 05/12/2021	TITLE: Fixed connector
		APPROVED: H. JIANG	DATE: 05/12/2021	CUSTOMER:

NINGBO CHANGYU ELECTRONICS MANUFACTURING CO., LTD  
 Email: sales@cymannu.com WWW.CYMANNU.COM